



the fuel storage experts

0005-160-CT000

Combination Diesel & AdBlue/DEF Tank
900/100 Litre (Diesel/AdBlue)



Fuel Proof Solutions

- **The NEW polyethylene tank for the combined transportation** of diesel fuel (900 litres) and AdBlue DEF fluid (100 litres) with **lockable** lid.
- **Carrytank 900+100 is the best** versatile tank on the market of this type, as it not only offers the convenience of storing two fluid types in one unit; this new tank has also successfully passed very stringent testing. This includes the testing required for **ADR/RID/ADN and IMDG approval**.

Key Points

- 4 x Lifting eyes and forklift pockets as standard
- Resistant to hits and shocks
- Resistant to low temperatures
- Resistant to UV ray exposure
- Ease of transport
- Combined fluid storage
- Removable AdBlue container
- Lockable top hinges





the fuel storage experts

0005-160-CT000

Combination Diesel & AdBlue/DEF Tank
900/100 Litre (Diesel/AdBlue)

Specification

Fuelling Performance

- Diesel - 12V DC horizontal inline port, approx. 40 litre per minute pump
- AdBlue/DEF - 12V DC submersible pump, approx. 20 litre per minute pump
- Both pump units run from a shared Anderson connector c/w female fitting

Compliance

- Road transport - ADR
- Transport on inland waters - ADN
- Transport by sea - IMDG
- Transport by rail - RID
- Stackable when full (maximum 2 units high, of same design & approval)

Tank Construction

- Single-skinned transport tank
- Minimum wall thickness - 10mm
- Diesel compartment capacity - 900 litres (first fill)
- AdBlue DEF compartment capacity - 100 litres (first fill)

Filtration

- Gauze strainer on suction side as standard
- **UPGRADE** - Inline fuel filter available on request

Moving/Lifting

- 4 x lifting eyes as standard; suitable for use when full
- Forklift pockets as standard; suitable for use when full

Measuring System

- Each tank has a volume level gauge as standard
- **UPGRADE** - Digital flow meter available on request

Hose

- Diesel - 4m dispensing hose as standard
- AdBlue/DEF - 4m dispensing hose as standard

Weights & Dimensions Approx.

- L - 1,550mm W - 1,150mm H - 910mm
- Weight empty - 100kg
- Weight including transfer kit 12V - 112kg

Paint System

- Fuel tank = Available in red or yellow Lid = Grey
- Exterior - Resistant to UV exposure

Safety Features

- Aluminium filling point, 2" in size with integrated air vent valve
- Emergency vent valves as standard
- Ergonomic lid hinges with 2 x locking points